


Flip Flop D-Type Pos-Edge 2-Element 14-Pin PDIP Tube

| | |
|----------------------|--|
| Manufacturer: | Texas Instruments, Inc |
| Package/Case: | DIP14 |
| Product Type: | Logic ICs |
| RoHS: | RoHS Compliant/Lead free  |
| Lifecycle: | Active |



Images are for reference only

[Inquiry](#)

General Description

The CD4013B device consists of two identical, independent data-type flip-flops. Each flip-flop has independent data, set, reset, and clock inputs and Q and Q outputs. These devices can be used for shift register applications, and, by connecting Q output to the data input, for counter and toggle applications. The logic level present at the D input is transferred to the Q output during the positive-going transition of the clock pulse. Setting or resetting is independent of the clock and is accomplished by a high level on the set or reset line, respectively.

The CD4013B types are supplied in 14-pin dual-in-line plastic packages (E suffix), 14-pin small-outline packages (M, MT, M96, and NSR suffixes), and 14-pin thin shrink small-outline packages (PW and PWR suffixes).

Key Features

Asynchronous Set-Reset Capability

Static Flip-Flop Operation

Medium-Speed Operation: 16 MHz (Typical) Clock Toggle Rate at 10-V Supply

Standardized Symmetrical Output Characteristics

Maximum Input Current Of 1- μ A at 18 V Over Full Package Temperature Range:
100 nA at 18 V and 25°C

Noise Margin (Over Full Package Temperature Range):
1 V at VDD = 5 V


2 V at VDD = 10 V

2.5 V at VDD = 15 V

Description

The CD4013B device consists of two identical, independent data-type flip-flops. Each flip-flop has independent data, set, reset, and clock inputs and Q and Q output to the data input, for counter and toggle applications. The logic level present at the D input is transferred to the Q output during the positive-going transition of the clock pulse. Setting or resetting is independent of the clock and is accomplished by a high level on the set or reset line, respectively.

The CD4013B types are supplied in 14-pin dual-in-line plastic packages (E suffix), 14-pin small-outline packages (M, MT, M96, and NSR suffixes), and 14-pin thin shrink small-outline packages (PW and PWR suffixes).



Recommended For You

CD4070BE

Texas Instruments, Inc

DIP14

CD74HCT138E

Texas Instruments, Inc

DIP16

CD4098BE

Texas Instruments, Inc

DIP

CD74HC08E

Texas Instruments, Inc

DIP

CD74HC4075E

Texas Instruments, Inc

DIP

CD74ACT74E

Texas Instruments, Inc

DIP-14

CD74HC75E

Texas Instruments, Inc

DIP

CD4504BE

Texas Instruments, Inc

DIP16

CD4068BE

Texas Instruments, Inc

DIP

CD4081BE

Texas Instruments, Inc

DIP14

CD4001BE

Texas Instruments, Inc

DIP14

CD4512BE

Texas Instruments, Inc

DIP16

CD4069UBE

Texas Instruments, Inc

DIP14

CD74HCT151E

Texas Instruments, Inc

DIP

CD74HC04M

Texas Instruments, Inc

SOP14