


Op Amp Single Low Power Amplifier R-R O/P $\pm 2.75V/5.5V$ 8-Pin SOIC Tube



Images are for reference only

[Inquiry](#)

Manufacturer: [Texas Instruments, Inc](#)

Package/Case: SOIC

Product Type: Amplifier ICs

RoHS: RoHS Compliant/Lead free 

Lifecycle: Active

General Description

The THS4531A device is a low-power, fully differential amplifier with input common-mode range below the negative rail and rail-to-rail output. The device is designed for low-power data acquisition systems and high-density applications where power consumption and dissipation is critical.

The device features accurate output common-mode control that allows for DC coupling when driving analog-to-digital converters (ADCs). This control, coupled with the input common-mode range below the negative rail and rail-to-rail output, allows for easy interface from single-ended ground-referenced signal sources to successive-approximation registers (SARs), and delta-sigma ($\Delta\Sigma$) ADCs using only single-supply 2.5-V to 5-V power. The THS4531A is also a valuable tool for general-purpose, low-power differential signal conditioning applications.

Key Features

UltraLow-Power:
Voltage: 2.5 V to 5.5 V

Current: 250 μ A

Power-Down Mode: 0.5 μ A(Typical)

Fully DifferentialArchitecture

Bandwidth: 36 MHz ($A_v = 1$ V/V)

Slew Rate: 200V/ μ s

THD: -120 dBc at 1 kHz (1 V_{RMS} , $R_L = 2$ k Ω)

Input VoltageNoise: 10 nV/ \sqrt{Hz} ($f = 1$ kHz)

High DCaccuracy:
VOS: $\pm 100\mu$ V

VOS Drift: ± 3 μ V/ $^{\circ}$ C (-40 $^{\circ}$ C to+125 $^{\circ}$ C)

AOL: 114dB

Rail-to-Rail Output(RRO)

Negative Rail Input (NRI)

Output Common-Mode Control

8-Pin SOIC (D) and VSSOP (DGK)

10-Pin WQFN (RUN)

All trademarks are the property of their respective owners.

Description

The THS4531A device is a low-power, fully differential amplifier with input common-mode range below the negative rail and rail-to-rail output. The device is designed for low-power data acquisition systems and high-density applications where power consumption and dissipation is critical.

The device features accurate output common-mode control that allows for DC coupling when driving analog-to-digital converters (ADCs). This control, coupled with the input common-mode range below the negative rail and rail-to-rail output, allows for easy interface from single-ended ground-referenced signal sources to successive-approximation registers (SARs), and delta-sigma ($\Delta\Sigma$) ADCs using only single-supply 2.5-V to 5-V power. The THS4531A is also a valuable tool for general-purpose, low-power differential signal conditioning applications.

Recommended For You

THS3092D

Texas Instruments, Inc

SOP-8

THS7316DR

Texas Instruments, Inc

SOP-8

THS4131IDGNR

Texas Instruments, Inc

MSOP8

THS4011CD

Texas Instruments, Inc

SOP

THS7374IPW

Texas Instruments, Inc

TSSOP14

THS6184RHFR

Texas Instruments, Inc

QFN

THS4503IDGN

Texas Instruments, Inc
MSOP8

THS7376IPWR

Texas Instruments, Inc
TSSOP14

THS7314D

Texas Instruments, Inc
SOP8

THS4130IDGK

Texas Instruments, Inc
MSOP8

THS7353PW

Texas Instruments, Inc
TSSOP20

THS4551IRGIR

Texas Instruments, Inc
VQFN16

THS4281D

Texas Instruments, Inc
SOIC-8

THS4631D

Texas Instruments, Inc
SOP-8

THS3061DGN

Texas Instruments, Inc
MSOP8